

# Technical Data Sheet

## Topadd® 135A

CPE-135A is general impact modifier with high molecular weight, superior mechanical performance; General impact modifier for rigid plastic products .

### Specification:

Items	UNIT	INDEX	Test Method
Chlorine content	%	35±1	ISO 7725
Heat of Fusion	J/g	≤2.0	DSC
Volatile Matter component	%	≤0.4	ISO 1269
Rate of filtration(40 mesh)	%	≥98	--
Shore Hardness A	°	≤65	ISO 7619
Thermal decomposition	°	≥170	--
Bulk density	g/cm3	≥0.5	--
Tensile strength	Mpa	≥8.0	ISO 37
Elongation at break	%	≥700	ISO 37
Impurity particle	PC/100g	<15	--
Filler content ,CaCO3	%	≤5.0	
Whiteness E457	°	≥80	--
Viscosity		95-105	

### Applications:

PVC door and window profiles, siding, sheet, fence, PVC pipe, electrical conduit etc.



PVC Sheet

PVC Sewer pipe

PVC Fence



PVC Threading Pipe

PVC Foaming products

PVC Bellow Pipe



PVC Profiles

Windows Profile

PVC Siding



Plastic & polymer additives and solution supplier  
E:info@novistagroup.com I : www.novistagroup.com

**Package and Storage:**

25kg PP valve bag ;  
25kg Woven bag with PE liner ;  
500/550kg super sack

The product can be stored under appropriate conditions for two years. But please keep products store in a dry ventilated environment (temperature should not exceed 30°C, in low humidity). Inappropriate storage environment may cause agglomeration.Especially at high temperatures & high humidity, it is recommended not to stack more than 30 days long, it may increase agglomeration phenomenon. Agglomeration does not affect the quality and performance , not a quality problem, but Agglomeration material is smashed before using .

It is not dangerous cargo .You should handle the material according to the instruction described on MSDS.The MSDS is available from sales department once required.

+86-536-8206760 [info@novistagroup.com](mailto:info@novistagroup.com) [www.novistagroup.com](http://www.novistagroup.com)

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Novista Group and its subsidiaries. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.