

Plastic & polymer additives and solution supplier E:info@novistagroup.com I: www.novistagroup.com

## Technical Data Sheet ProStab® NV-22312



## **Product Introduction**

22312 is one pack lead stabilizer for pvc rigid products such as pipe, sheet, panel and profile application. It is produced by metal compound stabilizer with the amount of chelating agent, lubricants and other internal and external components with the company's unique processing technology.

## **Product Properties**

It has good thermal stability and processing performance, reasonable formulation. It has excellent internal and external lubricating balance and has wide compatibility to different processing equipments.

Novista Code	System Base	Dosage
22312	One-pack lead	3.5-5.0

Appearance: White or yellowish Flake

Lead content:  $28.5 \pm 1.5$ Loss on heating: 1% max Initial melting point:  $85^{\circ}$  min

## **Package and Storage:**

Packed in 25kg pp woven bag (or according to customer's requirement)

- --Shelf-life in unopened bag is at least one year, if stored in a cool and dry place.
- --Do not expose bags to the weather. Opened bags should always be tightly sealed.
- -- Product in opened bags should be used as soon as possible.
- -- Do not pile up or move bags with metal hooks or sharp articles.

It is not dangerous cargo . You should handle the material according to the instruction described on SDS.

www.novistagroup.com info@novistagroup.com +86-536-8206760

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Novista Group and its subsidiaries. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.