

Plastic & polymer additives and solution supplier E:info@novistagroup.com I: www.novistagroup.com

Technical Data Sheet

ProFlame® PN3113

Specially for water-based acrylic coating adhesive

ProFlame-PN3113 is a formulated eco-friendly halogen-free flame retardant mainly based on phosphorus and nitrogen. It's an intumescent flame retardant in white powder form. With special surface coating treatment, PN3113 has good compatibility with the substrate, and good migration resistance.

Advantages:

- 1. achieving FR performance by both gas phase and solid phase mechanism
- 2. good colorability
- 3. no hydration, no blooming
- 4. good processability
- 5. low OVC content
- 6. no water stain with the final product
- 7. halogen-free, no harm to the environment and human body

Technical Data:

Items	Spec
Appearance	White free-flowing powder
P content, %	18-25
Decomposition Temperature, °C (TGA 1%)	≥320
Moisture,%	≤0.5
Average particle size (um, D50)	≤10
Specific gravity, g/cm3	1.3

Usage:

PN3113 is mainly used in various synthetic fibres and water-based acrylic coating adhesives.

Package:

PN3113 is delivered in paper-plastic compound bag, net weight 20 or 25±0.1kg per bag.

Storage and transportation:

Minimum shelf life is 12 months stored in a dry and ventilated warehouse.

+86-536-8206760 <u>info@novistagroup.com</u> <u>www.novistagroup.com</u>

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Novista Group and its subsidiaries. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.